

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
31 March 2005 (31.03.2005)

PCT

(10) International Publication Number  
**WO 2005/029802 A1**

(51) International Patent Classification<sup>7</sup>: **H04L 27/26**

(21) International Application Number:  
PCT/FI2003/000690

(22) International Filing Date:  
22 September 2003 (22.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **NOKIA CORPORATION** [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SCHWOERER, Ludwig** [DE/DE]; Mörikestr. 7, 45525 Hattingen (DE). **KAUFMANN, Andre** [DE/DE]; Hattinger Str. 344b, 44795 Bochum (DE). **VESMA, Jussi** [FI/FI]; Kirvesmiehenkuja 2, FIN-20320 Turku (FI).

(74) Agent: **BERGGREN OY AB**; P.O. BOX 16, FIN-00101 Helsinki (FI).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD, SYSTEM AND RECEIVER IN RECEIVING A MULTI-CARRIER TRANSMISSION



(57) Abstract: Mobile handheld terminals receiving DVB transmission require relatively low power consumption and TDM based transmission can be used to reduce power of the terminals. In order find pilot carrier position at least two symbols are accessed which are adapted to establish a correspondence pattern for pilot carriers in a matrix of the at least two symbols. Carriers of the first symbol are correlated with the corresponding carriers of the second symbol within the matrix for determining a correlation maximum for indicating a pilot carrier position.

WO 2005/029802 A1